


Spare Parts / Ersatzteile / Pièces de recharge / Pezzi di Ricambio / Piezas de requesto / Parte de reposição / Reserveonderdelen / Reservdelar / Reservedeler / Varaosat / Vraosat / Varahlutir / Ανταλλακτικά / Yedek Parçalar / Náhradní díly / Náhradné diely / Nadomestni deli / Резервни части / Запчасти / Części Zapasowe / Piese de schimb/ Rendelhető alkatrészek / Запасні частини / Reservni delovi / Резервни делови / Резервни делови / Atsarginių dalių / Tellitavad varuosad / Rezervju daļu


1	A 861 230 AA	1 Set
2	A 963 309 NU	1 pcs
3	B 960 473 AA	1 pcs
4	B 961 373 AA	1 pcs
5	B 961 374 NU	1 pcs
6	A 861 181 NU	1 pcs
7	A 861 156 NU*	1 Set
11	A 960 183 NU	2 pcs
13	A 962 005 NU	1 pcs
14	E 960 059 NU*	1 Set
16	A 960 935 AA	1 pcs
17	A 861 210 AA	1 Set
19	A 964 520 NU*	1 Set
20	A 961 172 NU	1 pcs
21	B 960 853 AA	1 Set







A7022 ..



A7054 ..


Connect Air


A7022 .. A7054 ..


0719 / A 868 365
(+ A 865 612)
Made in Germany

Ideal Standard International NV
Corporate Village - Gent Building
Da Vincilaan 2
1935 Zaventem
Belgium


www.idealstandardinternational.com


























Es ist systembedingt, daß während der Aufheizzeit Wasser durch Ausdehnung am Auslauf abtropft.
Dieser freie Austritt verhindert einen Druckanstieg im Speicher.
Es darf deshalb niemals der Auslauf verschlossen werden. Der Einbau eines Luftsprudlers
oder Schlauches mit Strahlregler ist nicht zulässig. Der im Batteriekörper eingebaute
Durchflußbegrenzer macht die Armatur unabhängig vom vorhandenen Wasserdruck.
Einregulieren der Wassermenge ist nicht erforderlich. Der Durchflußbegrenzer darf nicht entfernt werden!


As the water heats up, it will expand & possibly discharge through the outlet.
This water discharge is normal to prevent pressure damage to the hot water vessel.
DO NOT close this outlet. Aerator or hose with flow-straighter should not be used either.
The built in flow limiter regulates the supply water pressure, therefore it is not necessary to use
other regulating devices to control the flow. DO NOT remove the flow limiter!











P	bar	0,5 — MAX. 10	1 — 5	Q (3 bar)
T	°C	MAX. 85	40 — 65	l/min
				6